# MEGANITE <sup>®</sup> Acrylic Solid Surface

## 1. Identification

Product identifier	Meganite <sup>®</sup> AcryMed Series		
Other means of identification			
SDS number	01		
Synonyms	Not available.		
Recommended use	Surfacing material for horizontal and vertical applications.		
Recommended restrictions	Not available.		
Manufacturer/Importer/Supplier/Dist Manufacturer/Supplier	tributor information Meganite Inc.		
General Assistance E-Mail Emergency Telephone	info@meganite.com Contact your local health or emergency authority immediately.		

## 2. Hazard(s) Identification

Classification of the Product:

Not classified.

## \*Classification of the ingredient:

**\*Note:** The product in its finished, marketed form is believed to be inert and generally innocuous. These classifications/hazards are pertaining to a compromised/disrupted product due to operations and processing such as sanding, sawing, grinding, burning etc.

Physical hazards Health hazards	None Known Skin corrosion/irritation Serious eye damage/eye irritation Sensitization, Skin Specific target organ toxicity, single exposure; Respiratory tract irritation	Category 2 Category 2A Category 1 Category 3
Label elements		
Signal word	Warning	
Hazard statement	Causes skin irritation. Causes serious eye an allergic skin reaction. May cause resp	

cause



Precautionary statement	
Prevention	Wash skin thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing should not be allowed out of the workplace. Use only outdoors or in a well-ventilated area.
Response	IF ON SKIN: wash with plenty of soap and water. IF SKIN irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF eye irritation persists: Get medical advice/attention. IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. In case of fire: Use water or dry chemicals for extinction.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations. This product as sold in its marketed form is not considered an EPA hazardous waste when discarded. Allow hot or heated material to solidify and cool before disposal.
Hazard(s) not otherwise classified (HNOC)	None known.

# 3. Composition/information on ingredients

#### Mixtures

Chemical name	CAS number	%
Alumina Trihydrate	21645-51-2	Avg. 60
Acrylic Resin	N/A	Avg. 40
Colorant	N/A	<5
AdditivesN/A		<5

## 4. First-aid measures

#### **General notes:**

Consult a physician. Show this safety data sheet to the doctor in attendance.

# MEGANITE <sup>®</sup> Acrylic Solid Surface

-	
Inhalation	For overexposure to heated resins, remove from exposure. If breathing is difficult, or has stopped, administer artificial respiration (mouth-to-mouth) or oxygen as indicated. Call a physician, immediately.
Skin contact	Wash affected area with soap and plenty of water. Get medical attention if irritation develops or persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention.
Ingestion	Product in its marketed form is inert. If large amount are swallowed, call physician immediately.
Most important symptoms/effects, acute and delayed	Product sold in its marketed form is not expected to present a serious health hazard; however, operations such as sawing, sanding, grinding or burning may generate dust, smoke or vapors which may be irritating. Inhalation of such dusts, smoke and vapors may cause upper respiratory tract irritation. Symptoms may include burning sensation, coughing, sneezing, and sore throat. Skin contact with dust may produce transitory mechanical irritation. Symptoms may include redness and itching. High concentrations of dusts may cause irritation to the eyes causing burning, redness, and tearing. This product is not expected to be toxic if ingested. Prolonged or repeated skin contact may lead to allergic skin reactions. Prolonged or repeated over exposures to high concentrations may cause coughing, dizziness, confusion, headache and drowsiness. May affect the kidneys and liver.
Indication of immediate medical	In case of shortness of breath, give oxygen. Keep victim warm.
attention and special treatment needed	Keep victim under observation. Symptoms may be delayed.
General information	If exposed or concerned: get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use.

5. Fire-fighting measures	
Suitable extinguishing media	Use water or Dry chemical powder, Carbon dioxide (CO <sub>2</sub> ) and Foam.
Unsuitable extinguishing media	Do not use solid water stream as it may scatter and spread fire.
Fire and Explosion hazard	Avoid generating dust; fine dust dispersed in air in sufficient concentrations and in the presence of an ignition source is a potential dust explosion hazard. Hazardous combustion products may include carbon dioxide, carbon monoxide, methyl methacrylate monomer (MMA) Aldehydes and acrid smoke and fumes.



Special protective equipment and precautions for firefighters

Fire fighters should wear NIOSH/MSHA approved self-contained breathing apparatus and full protective clothing when fighting fires. Use cold water spray to cool fire-exposed containers.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Proper personal protective equipment should be utilized when handling this material. See Section 8 of the SDS for Personal Protective Equipment.
Methods and materials for containment and cleaning up	If released or spilled, product may be cleaned up and disposed in the trash. Allow hot or heated material to solidify and cool
	before disposal. Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into
	the atmosphere in sufficient concentration. Avoid dispersal of dust in the air (i.e. , cleaning dust surfaces with compressed air). Non-sparking tools should be used.

7. Handling and storage	
Handling (Personnel)	Do not breathe dust vapors of fumes that may be evolved during processing. Wash hands before breaks and at the end of workday. Minimize dust generation and accumulation. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Provide adequate precautions, such as electrical grounding and bonding or inert atmosphere.
Conditions for safe storage, including any incompatibilities	Store in cool dry area.

## 8. Exposure controls/personal protection

#### **Occupational exposure limits**

## US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Components	Туре	
Meganite 100% Acrylic Resin	PEL-TWA	-
Solid Surface		I

Value This product can generate Particulates Not Otherwise Regulated (PNOR). The OSHA PEL-TWA for PNOR is 15 mg/m3 (total dust) and 5 mg/m3 (respirable fraction).



Alumina Trihydrate	PEL-TWA	PNOC - 15 mg/m3 (total dust), 5 mg/m3 (respirable fraction)	
*Methyl Methacrylate (CAS#80-62-6)	PEL-TWA	100 ppm	
US. OSHA Table Z-1 Limits for Ai	r Contaminants	(29 CFR 1910.1000)	
Components	Туре	Value	
*Methyl Methacrylate (CAS#80-62-6)	8-hour TWA	100 ppm	
US. ACGIH Threshold Limit Value	es		
Components	Туре	Value	
Meganite 100% Acrylic Resin Solid Surface	TLV-TWA	The TLV-TWA for Particles Not Otherwise Specified (PNOS) is 10 mg/m3 (inhalable) and 3 mg/m3 (respirable fraction).	
Alumina Trihydrate	TLV-TWA	PNOC – 10 mg/m3 (inhalable), 3 mg/m3 (respirable fraction)	
*Methyl Methacrylate	TLV-TWA	50 ppm	
(CAS#80-62-6)	TLV-ST	100 ppm	
US. NIOSH: Pocket Guide to Chemical Hazards			
Components	Туре	Value	
*Methyl Methacrylate (CAS#80-62-6)	TWA	100 ppm	


Where governmentally imposed occupational exposure limits which are lower than the above figures are in effect, such limits shall take precedence.

\* Comment: At higher temperatures, small amounts of methyl methacrylate can be released.

Appropriate engineering controls	Local exhaust ventilation should be used to control the emissions of	
	air contaminants. General dilution ventilation may assist with the	
	reduction of air contaminant concentrations. It is recommended that	
	all dust control equipment such as local exhaust ventilation and	
	material transport systems involved in handling of this product	
	contain explosion relief vents or an explosion suppression system or	
	an oxygen deficient environment. Ensure that dust-handling systems	
	(such as exhaust dusts, dust collectors, vessels, and processing	
	equipment). Use only appropriately classified electrical equipment	
	and powdered industrial trucks.	



#### Individual protection measures, such as personal protective equipment



## 9. Physical and chemical properties

Appearance	Solid.
Physical state	Solid.
Form	Solid.
Color	Varies.
Odor	Odorless.
Odor threshold	Not available.
рН	Not available.
Melting point	Not available.
Freezing point	Not applicable.
Initial boiling point and boiling range	Not available.
Flash point	Not applicable.



Evaporation rate	Not available.
Flammability (solid, gas)	Not considered to be flammable.
Upper/lower flammability or explosive l	imits
Flammability limit – lower (%)	Not applicable.
Flammability limit – upper (%)	Not applicable.
Explosive limit - lower (%)	Not applicable.
Explosive limit - upper (%)	Not applicable.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Insoluble and also insoluble in Methanol, Diethyl ether, n-
	Octanol, Acetone.
Partition coefficient (n-octanol/water)	Insoluble.
Percent Volatile	Not applicable.
Air (% by volume)	Not applicable.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
-	

## 10. Stability and reactivity

Reactivity	Hazardous reactions will not occur under normal conditions.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions	Hazardous polymerization will not occur.
Conditions to avoid	Heat - Higher temperature can release methyl methacrylate.
Incompatible materials	Not reactive.
Hazardous decomposition Products	Carbon dioxide, carbon monoxide, acrid smoke and fumes, possibly methyl methacrylate.

### **11.** Toxicological information

**Product based information:** No toxicological information is available for the finished product. This product is generally believed to be inert based on available data.

#### \*Ingredient based information:

**\*Note:** This information are pertaining to a compromised/disrupted product due to operations and processing such as sanding, sawing, grinding, burning etc.



Information on likely routes of exposure:			
Ingestion Inhalation	This product is not expected to be toxic if ingested. Harmful if inhaled. Vapors may be irritating to the respiratory system and nasal passages.		
Skin contact	Contact of solid with dry skin causes mild irritation.		
Eye contact	Causes eye irritation and may injure eye tissue if not removed.		
Symptoms related to the physical, chemical and toxicological characteristics:	Burning sensation, coughing, sneezing, and sore throat. Skin redness and itching. Eye burning, redness, and tearing. Prolonged or repeated skin contact may lead to allergic skin reactions. Prolonged or repeated over exposures to high concentrations may cause coughing, dizziness, confusion, headache and drowsiness.		
Signs and Symptoms of Acute Overexposure:	Product sold in its marketed form is not expected to present a serious health hazard; however, operations such as sawing, sanding, grinding, or burning may generate dust, smoke or vapors which may be irritating. Inhalation of such dusts, smoke and vapor may cause upper respiratory tract irritation. Symptoms may include burning sensation, coughing, sneezing and sore throat. Skin contact with dust may produce transitory mechanical irritation. Symptoms may include redness and itching. High concentrations of dusts may cause irritation to the eyes causing burning, redness and tearing. This product is not expected to be toxic if ingested.		
Signs and Symptoms of Chronic Overexposure:	Prolonged or repeated over exposures to high concentrations may cause coughing, dizziness, confusion, headache and drowsiness. Prolonged or repeated skin contact may lead to allergic skin reactions.		
Medical Conditions Generally Aggravated By Exposure:	Individuals with chronic respiratory disorders may be adversely affected by any fume or airborne particulate matter exposure. Persons with preexisting skin disorders may be more susceptible to the effects of this material.		

Numerical measures of toxici	ty:				
Components	Test		Species	Test Results	
Alumina Trihydrate (CAS# 21645-51-2)	Oral LD <sub>5</sub>	50	Rat	>5000 mg/kg	
Methyl Methacrylate (CAS#	Oral LD <sub>5</sub>	50	Rat	7800 mg/kg	
80-62-6)	Dermal	LD <sub>50</sub>	Rabbit	> 5000 mg/kg	
	Inhalati	on LC <sub>50</sub>	Rat	15.375 mg/l - 29 mg/l	
Skin corrosion/irritation		Causes skin irritation.			
Serious eye damage/eye irritation Causes se		Causes ser	auses serious eye irritation.		
Respiratory or skin sensitizat	ion				
Respiratory sensitization Based on av		vailable data, the classification criteria are not met.			
Skin sensitization May ca		May cause	1ay cause an allergic skin reaction.		



Germ cell mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity	No data available.
IARC Monographs. Overall Evalua	ation of Carcinogenicity
Not listed.	
NTP Report on Carcinogens	
Not listed.	
US. OSHA Specifically Regulated S Not listed.	Substances (29 CFR 1910.1001-1050)
Reproductive toxicity	No data available.
Specific target organ toxicity - single exposure	May cause respiratory irritation.
Specific target organ toxicity - repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	No data available.

#### Additional information:

\*This product may contain certain inorganic pigments that may include compounds of nickel. Certain molecules of nickel have shown sufficient evidence of carcinogenicity (IARC Vol. 49) while others have shown limited or insufficient evidence of carcinogenicity in humans or animals. Titanium Dioxide: In lifetime inhalation studies of rats, airborne respirable-size titanium dioxide particles have been shown to cause lung tumors at concentrations associated with substantial particle lung burdens and consequential pulmonary overload and inflammation. However, other laboratory animals such as mice and hamsters did not develop lung tumors under similar testing with titanium dioxide. Furthermore, human epidemiology studies do not suggest an association between occupational exposure to titanium dioxide and risk for cancer. Under normal conditions of use and exposure, toxicological and epidemiological studies for titanium dioxide have shown no significant adverse health effects. Results of an epidemiology study showed that employees who had not been exposed to titanium dioxide were at no greater risk of developing lung cancer than were employees who had been exposed to titanium dioxide. No associations were observed between titanium dioxide exposure and chronic respiratory disease or lung abnormalities. Based on the results of this study, it was concluded that titanium dioxide will not cause lung cancer or chronic respiratory disease in humans at concentrations experienced in the work place.

## 12. Ecological information

Numerical measures of toxicityComponentsTeMethyl MethacrylateCi(CAS# 80-62-6)Ci

**Test** Crustacea EC<sub>50</sub>

Persistence and degradability Bioaccumulative potential Mobility in soil Not available. Not available. Not available.

Species Water flea (Daphnia magna)

**Test Results** 69 mg/l, 48 Hours



Not available.

13. Disposal considerations	
Disposal instructions	Dispose of in accordance with local, state and federal requirements. This product as sold in its marketed form is not considered an EPA hazardous waste when discarded. Allow hot or heated material to solidify and cool before disposal.

## 14. Transport information

**Other adverse effects** 

Not classified as dangerous in the meaning of transport regulations.

# 15. Regulatory information

US federal regulations TSCA Section 12(b) Export Not Not regulated. US. OSHA Specifically Regulat	tification (40 CFR 707, S	Subpt	. D)
Not listed.			
<b>CERCLA Hazardous Substance</b>	List (40 CFR 302.4)		
Methyl Methacrylate	(CAS# 80-62-6)	List	ed
Superfund Amendments and	Reauthorization Act of	1986	(SARA)
Hazard categories	Immediate Hazard	-	Yes
	Delayed Hazard	-	No
	Fire Hazard	-	No
	Pressure Hazard	-	No
	Reactivity Hazard	-	No
SARA 302 Extremely hazardou Not listed.	us substance		
SARA 311/312 Hazardous che	mical	Yes	
SARA 313 (TRI reporting)			
Methyl Methacrylate (CAS# 8	80-62-6)	List	ed
Nickel Compounds		List	ed
Other federal regulations Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List Not listed. Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) Not listed. Safe Drinking Water Act (SDWA) Not listed.			



#### **US State regulations:**

\*Warning, this product contains chemical(s) known to the state of California to cause cancer and/or birth defects or other reproductive harm. The Proposition 65 chemical(s) found in this product appear in trace amounts and would not be expected to pose significant risk: however, a risk assessment for this (these) chemical(s) has not yet been performed. Each product should be assessed in light of its use.

- US. Massachusetts RTK Substance List Methyl Methacrylate(CAS# 80-62-6)
- US. New Jersey Worker and Community Right-to-Know Act Methyl Methacrylate(CAS# 80-62-6)
- US. Pennsylvania Worker and Community Right-to-Know Law Methyl Methacrylate(CAS# 80-62-6)
- US. California Proposition 65 US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance Nickel Compounds listed.

Nickel Compounds list

## **Canada regulations**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR).

**WHMIS classification** 

D2

Materials Causing Other Toxic Effects.



International Inventories		
Country(s) or region	Inventory name	On inventory (yes/no) <sup>*</sup>
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non- Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemical List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States &	Toxic Substances Control Act (TSCA) Inventory	Yes



#### Puerto Rico

\*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

### 16. Other information, including date of preparation or last revision

Issue date Version #	1-Sep-2019 1			
NFPA AND HMIS Ratings	- NFPA Codes	HMIS Codes		
-	Health - 2	Health - 1		
	Flammability - 0	Flammability - 0		
	Reactivity - 0	Reactivity - 0		
References	ACGIH: Documentation of the Thresho	old Limit Values and Biological		
Exposure indices ECHA: European Chemicals Agency				
				HSDB: Hazardous Substances Data Bank
	IARC: International Agency for Research on Cancer NIOSH: The National Institute for Occupational Safety and Health NTP: National Toxicology Program NLM: Hazardous Substances Data Base			
	OECD: Organization for Economic Co-	operation and Development		
	OSHA: Occupational Safety and Health	Administration		

**Disclaimer:** The information, recommendations, and suggestions presented in this SDS are based upon test results and data believed to be reliable. The end user of the product has the responsibility for evaluating the adequacy of the data under the conditions of use, determining the safety, toxicity and suitability of the product under these conditions, and obtaining additional or clarifying information where uncertainty exists. No guarantee expressed or implied is made as to the effects of such use, the results to be obtained, or the safety and toxicity of the product in any specific application. Furthermore, the information herein is not represented as absolutely complete, since it is not practicable to provide all the scientific and study information in the format of this document, plus additional information may be necessary under exceptional conditions of use, or because of applicable laws or government regulations.

**Declare to reader:** If you require additional information regarding any legal or regulatory requirements referred to in this SDS, we suggest that you consult with an appropriate regulatory agency, or with a professional with expertise in this area. This information is taken from sources or based upon data believed to be reliable; however, Meganite Inc. makes no warranty as to the absolute correctness or sufficiency of any of the foregoing or that additional or other measures may not be required under particular conditions.