



A/C

PLYWOOD

At CMPC we are committed to provide high quality products and offer an excellent service. That is why we have been developing SELEX PLYWOOD; a stable and reliable Plywood panel with high quality and amazing appearance.

- Superior Quality.
- Continuous supply.



The mark of responsible forestry

* Ask about our FSC® certified products.



Decoration and furniture.



Interior and exterior decorative sheathing for walls and ceilings.



Packaging, furniture and lamination.

PRODUCT BENEFITS AND APPLICATIONS

- High quality visual panel, knot free, allowing the panel to be used for decorative applications, furniture making and flooring.
- Easy to handle due to excellent weight-volume ratio.
- CARB 2 compliant.

FEATURES

	Selex A	Selex C
Finishing		
Sanding grade	150	120
Natural defects		
Sound knots	Not allowed	Up to 40 mm wide
Unsound knots	Not allowed	Up to 40 mm wide
Knot holes	Not allowed	Up to 25 mm wide
Pitch pockets	Up to 10 mm wide	Allowed
Bark pockets	Not allowed	Allowed
Freckles	Solid without restriction	Allowed
Machining defects		
Open splits	Not allowed	Up to 25 mm wide
Open cracks	Not allowed	Up to 25 mm wide
Fungal stains	Slight	Allowed
Roughness	Slight	Allowed
Repairs		
Inner splits in knots	Repaired, up to 1 mm wide	Unrepaired, up to 1 mm wide
Routings with polyurethane	Very rarely	Allowed
Putty patches	Allowed	Not applicable
Single wooden patches	Up to 6	Not applicable
Double wooden patches	Up to 3	Not applicable
Triple wooden patches	Up to 2	Not applicable

GENERAL SPECIFICATIONS

Dimensions: 4' x 8' (1.22 x 2.44 m)	Thickness (mm)	6,5	9	12	15	18	21	25
	N° of plies	3	3	5	5	7	7	9
Density	29.96 - 34.26 Lbs / ft ³ (480 - 550 kg / m ³).							
Adhesive	CARB 2 compliant.							
Structural Certification	PS1 19 by TP & EN 13986 (CE2+) by HFB.							
Moisture Content	8% to 12 % for all boards.							
Forestry Certification	FSC® certified product.							